




Energy Rated Doors and Windows



4 Powell Street
Osborne Park



+61 8 9443-8311



enquiries@
glassworkx.com.au



www.glassworkx.
com.au



Glass Workx

Glass Workx (WA) Pty Ltd
4 Powell Street
OSBORNE PARK WA 6017
Tel: +61 8 9443-8311
E-mail: enquiries@glassworkx.com.au



**FLOOR TO CEILING DESIGNS
FOR MODERN LIVING.**



The ProGlide™ range has been designed with Australia's unique architecture and climate in mind. The door allows architects & designers to achieve large expansive openings whilst also offering a weather resistant wheelchair compliant sill to AS1428.1 without the need to compromise on performance or aesthetics.

This range of doors ensures that clients receive a solid, durable high performance product offering with an optional continuous accessible path of seamless transition between internal and external floor finishes.

Designed and manufactured in Australia to meet the extreme Australian Environment, the ProGlide™ range should be your first choice when performance and quality matter.



KEY FEATURES

- ⇒ AS1428.1 wheelchair compliant sill option.
- ⇒ Water resistant sill.
- ⇒ Large sliding panels.
- ⇒ Inside, outside sliding panels, allowing multiple panel designs.
- ⇒ Allows up to four (4) panels stacking in each direction.
- ⇒ Heavy duty aluminium profiles.
- ⇒ Accepts up to 14mm single glazed and up to 28mm double glazed units, allowing the system to achieve demanding thermal and acoustic specifications.
- ⇒ 90 degree post free corner option.

Maximum Recommended Sizes

Height	3000mm
Sash Width	1800mm
Weight	200kg per sash





Glass Workx

Glass Workx (WA) Pty Ltd
4 Powell Street
OSBORNE PARK WA 6017
Tel: +61 8 9443-8311
E-mail: enquiries@glassworkx.com.au



**MAXIMUM VIEW,
UNLIMITED POSSIBILITIES.**



The View-Max sliding and double-hung window offers unparalleled levels of flexibility by allowing the choice of 76mm or 101.6mm framing to cater for both the slimline applications and those of a more robust commercial design.

This range of windows offers the flexibility of single and double glazing options. The View-Max integrates a number of design initiatives that are unique to the system such as proprietary locking, roller and drainage systems.



KEY FEATURES

- ⇒ Designed with sliding & double-hung options to suit 76mm and 101.6mm framing.
- ⇒ Developed specifically for multi-storey residential and architecturally designed housing.
- ⇒ Accepts up to 11mm single glazed and up to 16mm double glazed units.
- ⇒ Superior thermal and acoustic performance.
- ⇒ Superior weather performance.
- ⇒ Simple fabrication makes these windows cost-effective.

Maximum Recommended Sizes

	Sliding	Double Hung
Height	1600mm	1190mm
Sash Width	1200mm	1200mm
Weight	50kg per sash	20kg per sash





MOTORISED GUILLOTINE WINDOWS AND DOORS

*A New Solution
for Windows and
Doors
“for a better
view”*



“Imagine a glass wall that virtually disappears to create a door or window function by sliding up or down, without taking up any space in its operation.”

The retractable architectural Guillotine Window and Door System represents a new paradigm to the architectural door and window world. The large spans and vertically retracting frames (up to 5,5m) provide unobstructed views and optimise the versatility of every opening in your buildings.

Put simply, they “broaden your horizons!”



Glass Workx (WA) Pty Ltd
4 Powell Street
OSBORNE PARK WA 6017

Tel.: 9443-8311
E-mail: enquiries@glassworkx.com.au
Web: www.glassworkx.com.au

One size does not suit all!

GUL - Lite Window & Door

- Economical alternative
- Single or double insulated glass
- Non thermally broken insulated framing
- Up to 20mm of glazing thickness
- Direct drive, 120Nm tubular motor
- Maximum retraction area of 12m²
- Maximum operable frame 140 kg
- Aesthetic look
- Minimalistic frames 125mm Motor Box



GUM - Medium Window & Door

- Best for residential and commercial projects
- Thermally broken profiles and frames
- Excellent thermal insulation, up to 1.6Uw
- Up to 32mm of glazing thickness
- Geared drive, 120Nm tubular motor
- Maximum retraction area of 16m²
- Maximum operable frame 300 kg
- Aesthetic look
- Minimalistic frames



GUG - Grand Window & Door

- Best for large opening and commercial operation
- Thermally broken profiles and frames
- Excellent thermal insulation, up to 1.6Uw
- Up to 32mm of glazing thickness
- 3 phase 0.55 Kva Screw drive operation
- Maximum retraction area of 25m²
- Maximum operable frame 600 kg
- Aesthetic look



Guillotine Door



Guillotine Window



Glass Workx (WA) Pty Ltd Registered Dealer for



LIBART



Glass Workx

Glass Workx (WA) Pty Ltd
4 Powell Street
OSBORNE PARK WA 6017
Tel: +61 8 9443-8311
E-mail: enquiries@glassworkx.com.au



**UNINTERRUPTED VIEW,
MAXIMUM VENTILATION.**



The ProVista™ Sashless Double Hung window offers unobstructed views whether the window is open or not. The two panes of glass slide smoothly and effortlessly past each other with a minimalist design.

It creates a clean and modern aesthetic feel while also providing maximum ventilation.

KEY FEATURES

- ⇒ 2, 3 and 4 pane configurations.
- ⇒ New build and retrofit compatible.
- ⇒ Snap in jambs providing concealed fixings and pulleys.
- ⇒ Vent lock and key locking options.
- ⇒ Excellent weather, bushfire, acoustic and energy performance.

Maximum Recommended Sizes		
Sash Height	1800mm	
Sash Width	Dependant on sash weights	
Sash Weight	Std Pulley	Wide Pulley
	25kg	40kg





Glass Workx

Glass Workx (WA) Pty Ltd
4 Powell Street
OSBORNE PARK WA 6017
Tel: +61 8 9443-8311
E-mail: enquiries@glassworkx.com.au



**SUPERIOR WEATHER
PERFORMANCE AND EXCELLENT
THERMAL & ACOUSTIC GRADE.**



The ProTilt™ High Performance Awning and Casement windows are ideally suited for residential, hotel and commercial applications.

Featuring overlapping internal and external seals, the ProTilt™ window is the preferred choice where superior weather performance is required. A range of glass thickness options from 5mm to 28mm allows the system to be configured for excellent thermal and acoustic performance.

The system can be used with a range of available stays while offering multi-point locking options and a proprietary winder.



KEY FEATURES

- ⇒ Concealed multi-point locking.
- ⇒ Superior weather performance.
- ⇒ Accepts up to 16mm single glazed and up to 28mm double glazed units, allowing the system to achieve the most demanding thermal and acoustic specifications.
- ⇒ Excellent thermal and acoustic performance.

Maximum Recommended Sizes

	Awning	Casement
Max Height	2000mm	2100mm
Min Height	400mm	900mm
Max Width	1500mm	1000mm
Min Width	500mm	500mm
Max Area	2.4m ²	2.0m ²
Max Weight	136kg	49kg

